

**HAVILAND CONSUMER PRODUCTS, INC**  
**SAFETY DATA SHEET**



**Section 1: Identification**

Product Name: Spa Pure Water Hardness Inc. Product Code: C002729

Haviland Consumer Products, Inc.  
421 Ann Street NW  
Grand Rapids, MI 49504  
(616) 361-6691

**Emergency Phone**  
CHEMTREC (800) 424-9300  
CHEMTREC International (703) 527-3887

Product Use: Swimming Pool  
Not recommended for: No data available

**Section 2: Hazard(s) Identification**

**GHS Ratings:**

Oral Toxicity	Acute Tox. 4	Oral>300+<=2000mg/kg
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
Organ toxin single exposure	3	Transient target organ effects- Narcotic effects- Respiratory tract irritation
Organ toxin repeated exposure	2	Presumed to be harmful to human health- Animal studies with significant toxic effects relevant to humans at generally moderate exposure (guidance)- Human evidence in exceptional cases

**GHS Hazards**

H302	Harmful if swallowed
H315	Causes skin irritation
H318	Causes serious eye damage
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure

**GHS Precautions**

P260	Do not breathe dust/fume/gas/mist/vapors/spray
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash face, hands, and any exposed skin thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves/protective clothing/eye protection/face protection
P310	Immediately call a POISON CENTER or doctor/physician
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P314	Get Medical advice/attention if you feel unwell
P321	Specific treatment (see first aid treatment on SDS)
P330	Rinse mouth

P362	Take off contaminated clothing and wash before reuse
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
P302+P352	IF ON SKIN: Wash with soap and water
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P332+P313	If skin irritation occurs: Get medical advice/attention
P405	Store locked up
P403+P233	Store in a well ventilated place. Keep container tightly closed
P501	Dispose of contents/container in accordance with local/regional/national/international regulations

**Danger**



**Section 3: Composition/Information on Ingredients**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Trade Secret 80 to 90%			
Potassium chloride 7447-40-7 1 to 5%			
Trade Secret 1 to 5%			

**Section 4: First-aid Measures**

**Inhalation**

Fresh air should alleviate any respiratory discomfort. If breathing difficulties develop or persist, get medical attention.

**Eye Contact**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If effects occur, consult a physician, preferably an ophthalmologist. May cause injury due to mechanical action.

**Skin Contact**

Flush with water for at least 15 minutes while removing contaminated clothing. If irritation persists, get medical attention.

**Ingestion**

If swallowed, do not induce vomiting. Give one cup (8 ounces or 240 ml) of water or milk if available and transport to a medical facility. Never give anything by mouth to an unconscious or convulsive person.

**Section 5: Fire-fighting Measures**

Flash Point: N/A

LEL:

UEL:

**Extinguishing Media**

Use media suitable for the surrounding fires.

**Specific Hazards Arising from the Chemical**

The product itself does not burn. When calcium chloride is being dissolved in water, large amounts of heat develop .

**Special Protective Equipment and Precautions for Firefighters**

Keep unnecessary people away, isolate hazard area and deny entry . This material does not burn. Fight fire for other material that is burning. Water should be applied in large quantities as fine spray . Wear NIOSH approved positive-pressure self-contained breathing apparatus operated in pressure demand mode. Wear protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations.

**Section 6: Accidental Release Measures**

Wear appropriate protective equipment and clothing during clean up . Sweep spill and transfer material into appropriate container(s) for disposal.

**Section 7: Handling and Storage**

**Precautions for safe handling**

Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling . Heat developed during diluting or dissolving is very high. Use cool water when diluting or dissolving (temperature less than 80°F, 27°C) . Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Keep container tightly closed when not in use.

**Conditions for safe storage, including any incompatibilities**

Keep container closed. Store in a dry place. Protect from atmospheric moisture.

**Section 8: Exposure Control/Personal Protection**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Trade Secret N/A			
Potassium chloride 7447-40-7			
Trade Secret N/A			

**Engineering Controls**

Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

**Eye Protection**

Wear safety glasses with side-shields. For dusty operations or when handling solutions of the material, wear chemical goggles.

**Respiratory Protection**

If ventilation is not sufficient to effectively prevent buildup of dust, appropriate NIOSH/MSHA particulate respirator must be provided.

**Skin and Body Protection**

Wear chemical resistant gloves, footwear, and protective clothing appropriate for the risk exposure .

## Section 9: Physical and Chemical Properties

<p><b>Evaporation rate:</b> Unknown</p> <p><b>Explosive Limits:</b> Unknown</p> <p><b>Autoignition temperature:</b> Unknown</p> <p><b>Viscosity:</b> Unknown</p> <p><b>Appearance:</b> White flakes</p> <p><b>Vapor Pressure:</b> Negligible at ambient temperature</p> <p><b>Vapor Density:</b> Unknown</p> <p><b>Density:</b> Unknown</p> <p><b>Freezing point:</b> Unknown</p> <p><b>Boiling range:</b> Unknown</p>	<p><b>Flammability:</b> Unknown</p> <p><b>Specific Gravity:</b> Unknown</p> <p><b>Decomposition temperature:</b> Unknown</p> <p><b>Grams VOC less water:</b> Unknown</p> <p><b>Odor:</b> Odorless</p> <p><b>Odor threshold:</b> Unknown</p> <p><b>pH:</b> Unknown</p> <p><b>Melting point:</b> 260°C (500°F)</p> <p><b>Solubility:</b> readily soluble</p> <p><b>Flash point:</b> Unknown</p>
--	---

## Section 10: Stability and Reactivity

### Stability

STABLE

### Incompatible Materials

Heat is generated when mixed with water. Spattering and boiling can occur. Avoid contact with: Sulfuric acid. Corrosive when wet. Flammable hydrogen may be generated from contact with metals such as: Zinc. Sodium. Reaction of bromide impurity with oxidizing materials may generate trace levels of impurities such as bromate.

### Conditions to Avoid

Avoid conditions of moisture.

### Hazardous Decomposition Products

Does not decompose

Hazardous polymerization will not occur.

## Section 11: Toxicology Information

### Mixture Toxicity

Oral Toxicity LD50: 1,191mg/kg

Dermal Toxicity LD50: 3,204mg/kg

### Component Toxicity

### Routes of Entry

### Effects of Overexposure

#### Acute Toxicity

Inhalation: Dust may cause irritation to upper respiratory tract (nose and throat).

Skin contact: Brief contact is essentially nonirritating to skin. Prolonged contact may cause skin irritation, even a burn. Not classified as corrosive to the skin according to DOT guidelines. May cause more severe response if skin is damp. May cause more severe response if skin is abraded (scratched or cut). May cause more severe response on covered skin (under clothing, gloves).

Eye contact: For solid: May cause slight eye irritation, mechanical injury only. Dust formation should be avoided, as dust can cause severe eye irritation with corneal injury.

Ingestion: Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. Swallowing may

result in gastrointestinal irritation or ulceration.

#### Chronic Effects

For the minor component(s): Potassium chloride - In animals, effects have been reported on the following organs after ingestion: Gastrointestinal tract, Heart, and Kidney. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use. Medical experience with sodium chloride has shown a strong association between elevated blood pressure and prolonged dietary overuse. Related effects could occur in the kidneys.

#### Carcinogenicity

This product is not classified as a carcinogen by NTP, IARC or OSHA.

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
-------------------	--------------------	-----------------	--------------------------

#### Section 12: Ecological Information

#### Component Ecotoxicity

Trade Secret	96 Hr LC50 Lepomis macrochirus: 10650 mg/L [static] 48 Hr LC50 Daphnia magna: 2400 mg/L
Potassium chloride	96 Hr LC50 Lepomis macrochirus: 1060 mg/L [static]; 96 Hr LC50 Pimephales promelas: 750 - 1020 mg/L [static] 48 Hr EC50 Daphnia magna: 825 mg/L; 48 Hr EC50 Daphnia magna: 83 mg/L [Static] 72 Hr EC50 Desmodesmus subspicatus: 2500 mg/L
Trade Secret	96 Hr LC50 Lepomis macrochirus: 5560 - 6080 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 12946 mg/L [static]; 96 Hr LC50 Pimephales promelas: 6020 - 7070 mg/L [static]; 96 Hr LC50 Pimephales promelas: 7050 mg/L [semi-static]; 96 Hr LC50 Pimephales promelas: 6420 - 6700 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4747 - 7824 mg/L [flow-through] 48 Hr EC50 Daphnia magna: 1000 mg/L; 48 Hr EC50 Daphnia magna: 340.7 - 469.2 mg/L [Static]

#### Section 13: Disposal Considerations

Dispose of in accordance with all Federal, State and local regulations

#### Section 14: Transportation Informations

Refer to bill of lading or container label for DOT or other transportation hazard classification, if any .

#### Section 15: Regulatory Information

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
----------------	-------------------	------------------------------

#### Section 16: Other Information

Date Prepared: 7/23/2015

Reviewer Revision

#### Disclaimer

The information herein is believed to be correct, but does not claim to be all inclusive and should be used only as a guide. Neither the above named supplier nor any of its affiliates or subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All chemical reagents must be handled with the recognition that their chemical, physiological, toxicological, and hazardous properties have not been fully investigated or determined. All chemical reagents should be handled only by individuals who are familiar with their potential hazards and who have been fully trained in proper safety, laboratory, and chemical handling procedures . Although certain hazards are described herein,

we can not guarantee that these are the only hazards which exist. Our SDS are based only on data available at the time of shipping and are subject to change without notice as new information is obtained. Avoid long storage periods since the product is subject to degradation with age and may become more dangerous or hazardous. It is the responsibility of the user to request updated SDS for products that are stored for extended periods. Disposal of unused product must be undertaken by qualified personnel who are knowledgeable in all applicable regulations and follow all pertinent safety precautions including the use of appropriate protective equipment (e.g. protective goggles, protective clothing, breathing equipment, face mask, fume hood). For proper handling and disposal, always comply with federal, state and local regulations.